

# MATERIAL SAFETY DATA SHEET

## SECTION 1 – COMPANY AND PRODUCT IDENTIFICATION

**Golden Artist Colors, Inc.**  
188 Bell Road  
New Berlin, NY 13411

**Date Revised:** 3/7/2017  
**Phone:** (607)847-6154  
**Prepared by:** Ben Gavett

### GOLDEN PAINTWORKS LIFESTYLEFINISHES

PRODUCT NAME	MAX. VOC
TEXTURES	
000D350 Weathered Granite Texture	50
000D352 Adobe Texture	50
000D345 Metallic Pearl Texture	50
000D354 Fresco Texture	50
000D356 Soapstone Texture	50
000D346 Metallic Gold Texture	50
000D359 Glass Bead Texture	50
000D360 Glass Bead XL Texture	50
000D361 Cut Sandstone Texture	50
000D362 Stucco Texture	50
000D364 Venetian Plaster Texture	50
METALLICS	
000D294 Bronze	350
000D295 Copper	350
000D296 Gold	350
000D297 Pearl	350
OTHER	
000D422 Protective Sealing Wax	700
000D203 Glazing Medium	700

## SECTION 2 - HAZARD IDENTIFICATION

**OSHA/HCS STATUS:** Non-Hazardous

**CLASSIFICATION:** Does not meet hazard classification criteria

### HAZARDS NOT OTHERWISE CLASSIFIED:

Irritation of the nose, throat and lungs is associated with excessive exposure to ammonia, which may occur when large volumes of product are used in an area with limited ventilation. Metallic Mediums contain a mica-based metallic pigment which, if chronically inhaled as a spray mist, could result in lung fibrosis.

**EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** Contact may cause mild to moderate irritation. Textural products may cause mechanical eye irritation and abrasion.

**SKIN CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** Prolonged or repeated contact may be irritating to skin.

000D352 Adobe Texture: Skin contact may be irritating and result in contact dermatitis

**ADDITIONAL HAZARDS ASSOCIATED WITH SPECIFIED PIGMENTS OR THEIR COMPONENTS IDENTIFIED IN SECTION 3:**

CRYSTALLINE SILICA- Considered a carcinogen through inhalation overexposure. Also a known cause of silicosis, a noncancerous lung disease. **WARNING:** This product contains a chemical known to the State of California to cause cancer. (Applies to airborne particles of respirable size only)

***SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS***

<b>PRODUCT</b>		<b>Max</b>	
		<b>%</b>	
All	Ammonia	1	7664-41-7
000D352	Calcium Meta-Silicate	25	13983-17-0
000D352	Crystalline Silica	25	14808-60-7
000D354	Crystalline Silica	10	14808-60-7
000D361	Crystalline Silica	20	14808-60-7
000D362	Crystalline Silica	40	14808-60-7

***SECTION 4 - FIRST AID MEASURES***

**EYE CONTACT:** Flush with water for 15 minutes. SEE DOCTOR if any symptoms persist.

**SKIN CONTACT:** Wash with soap and water. SEE DOCTOR if skin irritation occurs.

**INHALATION:** Remove subject to fresh air. SEE DOCTOR if symptoms persist

**INGESTION:** If swallowed, dilute by giving 2 or more glasses of water to drink **ONLY IF CONSCIOUS!** SEE DOCTOR.

***SECTION 5 - FIRE FIGHTING MEASURES***

**FLASH POINT:** None

**METHOD USED:** N/A

**FLAMMABLE LIMITS IN AIR BY VOLUME:**

**LOWER:** N/A **UPPER:** N/A

**EXTINGUISHING MEDIA:** Carbon dioxide, water spray, foam or dry chemical.

**SPECIAL FIRE FIGHTING PROCEDURES:** Use self-contained breathing apparatus and full protective clothing.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Decomposition and combustion products may be toxic.

***SECTION 6 – ACCIDENTAL RELEASE MEASURES***

Contain spill. Recover material for use or proper disposal. Clean residue with aqueous mopping.

## ***SECTION 7 - HANDLING AND STORAGE***

Protect from freezing

## ***SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION***

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMAN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**RESPIRATORY PROTECTION:** None required under normal use. When sanding or spraying, use a NIOSH P100 dust and mist respirator. If conditions warrant, a vapor respirator for protection against ammonia may be used.

**VENTILATION:** General dilution ventilation is recommended at a level sufficient to keep individuals asymptomatic to inhalation exposure.

**PROTECTIVE GLOVES:** Gloves are recommended.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Safety glasses (with side shields) or goggles

**WORK/HYGIENIC PRACTICES:** All products should be used in accordance with safe handling practices, including: do not eat, drink or smoke when working with materials, avoid excessive skin contact, wash after working with materials.

## ***SECTION 9 - PHYSICAL/CHEMICAL PROPERTIES***

**BOILING POINT:** >100°C/212°F

**SPECIFIC GRAVITY (H<sub>2</sub>O=1):** Varies

**VAPOR DENSITY:** Heavier than air

**pH:** 8.5-9.2

**SOLUBILITY IN WATER:** Miscible

**APPEARANCE AND ODOR:** Milky white or colored- slight ammonia odor

## ***SECTION 10 - STABILITY AND REACTIVITY***

**STABILITY:** Stable

**INCOMPATIBILITY:** May react with strong oxidizers

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS:** NA

## ***SECTION 11 – TOXICOLOGICAL INFORMATION***

Not tested as a whole, classification determination based on individual components

## ***SECTION 12 – ECOLOGICAL INFORMATION***

Not readily biodegradable. No other data available.

### ***SECTION 13 – DISPOSAL CONSIDERATIONS***

Dispose as per local regulations. It is best to use all material, rather than dispose of it. If necessary, dispose of as nonhazardous latex paint.

### ***SECTION 14 -TRANSPORT INFORMATION***

NOT REGULATED FOR TRANSPORT BY IATA, IMDG OR DOT.

### ***SECTION 15 – REGULATORY INFORMATION***

Contact us for additional information

### ***SECTION 16 – OTHER INFORMATION***

3/7/2017

New