# SAFETY DATA SHEET

# SECTION 1 – COMPANY AND PRODUCT IDENTIFICATION

Golden Artist Colors, Inc.

188 Bell Road New Berlin, NY 13411 **Date Revised:** 7/12/2018 **Phone:** (607)847-6154 **Prepared by:** Ben Gavett

### GOLDEN PAINTWORKS MURAL PAINTS

Burnt Sienna Burnt Umber Carbon Black Chrome Oxide Green Dioxazine Purple Hansa Yellow Opaque Phthalo Blue GS
Phthalo Green BS
Pyrrole Red
Quinacridone Magenta
Raw Sienna
Raw Umber
Titanium White
Ultramarine Blue
Daylight Blue
Pyrrole Orange
Yellow Oxide
Bismuth Vanadate Yellow
Pyrrole Red Light
Pyrrole Red Dark
Sap Green Hue
Light Yellow
Medium Yellow
Yellow Orange
Medium Green
Yellow Green
Light Yellow Green
Hookers Green Hue
Quinacridone VIolet
Crimson
Light Blue GS
Royal Blue
Purple

Payne's Gray
Iridescent Pearl
Iridescent Silver
Iridescent Gold
Iridescent Copper
Iridescent Bronze

# SECTION 2 - HAZARD IDENTIFICATION



WARNING: May cause an allergic skin reaction.

#### HAZARDS NOT OTHERWISE CLASSIFIED:

Irritation of the nose, throat and lungs is associated with excessive exposure to ammonia, which may occur when large volumes of product are used in an area with limited ventilation. Contact may be slightly irritating to eyes.

Overexposure to dusts and mists from sanding and spraying may be irritating to the respiratory tract. Chronic exposure to dusts and mists may cause pulmonary diseases.

#### SECTION 3 - COMPONENT INFORMATION

<u>COLOR</u>		% Compound	CAS #	
ALL COLORS	<.5 3-iodo-2-propynyl buty	lcarbamate	55406-53-6	Skin Sens. 1, H317
CPWSM01	Burnt Sienna <sup>1</sup>	<1 Quartz	14808-60-7	Carc. 1A, H350
CPWSM02	Burnt Umber <sup>1</sup>	<1 Quartz	14808-60-7	Carc. 1A, H350
CPWSM12	Raw Sienna <sup>1</sup>	<1 Quartz	14808-60-7	Carc. 1A, H350
CPWSM13	Raw Umber <sup>1</sup>	<1 Quartz	14808-60-7	Carc. 1A, H350
CPWSM03	Carbon Black <sup>1</sup>	<2 Carbon Blac	ck 1333-86-4	Carc. 2, H351
CPWSM25	Sap Green Hue <sup>1</sup>	<.5 PY150	68511-62-6	Carc. 1A, H350
CPWSM32	Hookers Green Hue <sup>1</sup>	<.5 PY150	68511-62-6	Carc. 1A, H350
CPWSM39	Payne's Gray <sup>1</sup>	<1 Carbon Blac	rk 1333-86-4	Carc. 2, H351

<sup>1</sup>WARNING: This product contains a chemical known to the State of California to cause cancer.

- H317 May Cause an Allergic Skin Reaction
- H350 May Cause Cancer
- H351 Suspected of Causing Cancer

#### **SECTION 4 - FIRST AID MEASURES**

**EYE CONTACT:** Flush with water for 15 minutes. SEE DOCTOR if any symptoms persist. **SKIN CONTACT:** Wash with soap and water. SEE DOCTOR if skin irritation occurs. **INHALATION:** Remove subject to fresh air. SEE DOCTOR if symptoms persist **INGESTION:** If swallowed, dilute by giving 2 or more glasses of water to drink ONLY IF CONSCIOUS! SEE DOCTOR.

# SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: None METHOD USED: N/A FLAMMABLE LIMITS IN AIR BY VOLUME: LOWER: N/A UPPER: N/A **EXTINGUISHING MEDIA:** Carbon dioxide, water spray, foam or dry chemical. SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus and full protective clothing. **UNUSUAL FIRE AND EXPLOSION HAZARDS:** Decomposition and combustion products may be toxic.

# SECTION 6 – ACCIDENTAL RELEASE MEASURES

Contain spill. Recover material for use or proper disposal. Clean residue with aqueous mopping.

# SECTION 7 - HANDLING AND STORAGE

For best product stability, avoid freezing and higher than normal ambient temperatures.

# SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION

**RESPIRATORY PROTECTION:** None required under normal use. When sanding or spraying, use a NIOSH P100 dust and mist respirator. If conditions warrant, a vapor respirator for protection against ammonia may be used.

**VENTILATION:** General dilution ventilation is recommended at a level sufficient to keep individuals asymptomatic to inhalation exposure.

PROTECTIVE GLOVES: None required under normal use. For techniques requiring continual hand exposure, gloves are recommended.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** None required under normal use.

WORK/HYGIENIC PRACTICES: Used in accordance with safe handling practices, including: do not eat, drink or smoke when working with materials, avoid excessive skin contact, wash after working with materials.

# SECTION 9 - PHYSICAL/CHEMICAL PROPERTIES

**BOILING POINT:** >100°C/212°F **SPECIFIC GRAVITY (H20=1):** 1.09-1.28 **VAPOR DENSITY:** Heavier than air **pH:** 8.5-9.2 **SOLUBILITY IN WATER:** Miscibile APPEARANCE AND ODOR: Milky white or colored- slight ammonia odor **VOC:** <50 g/l

# SECTION 10 - STABILITY AND REACTIVITY

**STABILITY:** Stable **INCOMPATIBILITY:** May react with strong oxidizers **HAZARDOUS DECOMPOSITION OR BYPRODUCTS**Ultramarine Blue acids to form flammable and toxic hydrogen sulfide.

# SECTION 11 – TOXICOLOGICAL INFORMATION

Product not evaluated as a whole. Classification based on individual components.

# SECTION 12 – ECOLOGICAL INFORMATION

Not readily biodegradable. No other data available.

# SECTION 13 – DISPOSAL CONSIDERATIONS

Dispose as per local regulations. It is best to use all material, rather than dispose of it. If necessary, dispose of as latex paint.

# SECTION 14 -TRANSPORT INFORMATION

Not hazardous for shipping via any mode

# SECTION 15 – REGULATORY INFORMATION

Contact us for further information.

# SECTION 16 – OTHER INFORMATION

7/12/2017 New