

SAFETY DATA SHEET

SECTION 1 – COMPANY AND PRODUCT IDENTIFICATION

Golden Artist Colors, Inc.
188 Bell Road
New Berlin, NY 13411

Date Revised: 7/12/2018
Phone: (607)847-6154
Prepared by: Ben Gavett

GOLDEN PAINTWORKS THEME PAINTS

CPWTP01	Burnt Sienna
CPWTP02	Burnt Umber
CPWTP03	Carbon Black
CPWTP04	Chrome Oxide Green
CPWTP06	Dioxazine Purple
CPWTP08	Phthalo Blue GS
CPWTP09	Phthalo Green BS
CPWTP10	Pyrrole Red
CPWTP12	Raw Sienna
CPWTP13	Raw Umber
CPWTP14	Titanium White
CPWTP17	Pyrrole Orange
CPWTP18	Yellow Oxide
CPWTP22	Bismuth Vanadate Yellow
CPWTP23	Pyrrole Red Light
CPWTP24	Pyrrole Red Dark
CPWTP25	Sap Green
CPWTP27	Medium Yellow
CPWTP28	Yellow Orange
CPWTP29	Medium Green
CPWTP30	Yellow Green
CPWTP32	Hookers Green Hue
CPWTP34	Quinacridone Violet
CPWTP38	Purple
CPWTP60	Iridescent Pearl
CPWTP61	Iridescent Silver
CPWTP62	Iridescent Gold
CPWTP63	Iridescent Copper
CPWTP64	Iridescent Bronze
CPWTP80	Iridescent Statuary Bronze
CPWTP81	Iridescent Pale Gold
CPWTP82	Iridescent Champagne
CPWTP76	Moss Yellow

CPWTP77	Phthalo Blue RS
CPWTP78	Medium Green
CPWTP19	Transparent Red Iron Oxide
CPWTP20	Transparent Yellow Iron Oxide
CPWTP21	Transparent Brown Iron Oxide
CPWTP79	Transparent Carbon Black
CPWTP83	Transparent Black Oxide
CPWTPB1	Base 1 Pastel
CPWTPB2	Base 2 Tint
CPWTPB3	Base 3 Deep
CPWTPB4	Base 4 Neutral

SECTION 2 - HAZARD IDENTIFICATION



WARNING: May cause an allergic skin reaction.

HAZARDS NOT OTHERWISE CLASSIFIED:

Irritation of the nose, throat and lungs is associated with excessive exposure to ammonia, which may occur when large volumes of product are used in an area with limited ventilation. Contact may be slightly irritating to eyes.

Overexposure to dusts and mists from sanding and spraying may be irritating to the respiratory tract. Chronic exposure to dusts and mists may cause pulmonary diseases.

SECTION 3 - COMPONENT INFORMATION

<u>COLOR</u>		<u>% Compound</u>	<u>CAS #</u>	
ALL COLORS	<.5 3-iodo-2-propynyl butylcarbamate		55406-53-6	Skin Sens. 1, H317
CPWTP01	Burnt Sienna ¹	<1 Quartz	14808-60-7	Carc. 1A, H350
CPWTP02	Burnt Umber ¹	<1 Quartz	14808-60-7	Carc. 1A, H350
CPWTP12	Raw Sienna ¹	<1 Quartz	14808-60-7	Carc. 1A, H350
CPWTP13	Raw Umber ¹	<1 Quartz	14808-60-7	Carc. 1A, H350
CPWTP03	Carbon Black ¹	<2 Carbon Black	1333-86-4	Carc. 2, H351
CPWTP79	Transparent Carbon Black ¹	<1 Carbon Black	1333-86-4	Carc. 2, H351
CPWTP25	Sap Green ¹	<.5 PY150	68511-62-6	Carc. 1A, H350
CPWTP32	Hookers Green Hue ¹	<.5 PY150	68511-62-6	Carc. 1A, H350

WARNING: This product contains a chemical known to the State of California to cause cancer.

H317	May Cause an Allergic Skin Reaction
H350	May Cause Cancer
H351	Suspected of Causing Cancer

SECTION 4 - FIRST AID MEASURES

EYE CONTACT: Flush with water for 15 minutes. SEE DOCTOR if any symptoms persist.

SKIN CONTACT: Wash with soap and water. SEE DOCTOR if skin irritation occurs.

INHALATION: Remove subject to fresh air. SEE DOCTOR if symptoms persist

INGESTION: If swallowed, dilute by giving 2 or more glasses of water to drink ONLY IF CONSCIOUS!
SEE DOCTOR.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: None

METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME: LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: Carbon dioxide, water spray, foam or dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Decomposition and combustion products may be toxic.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Contain spill. Recover material for use or proper disposal. Clean residue with aqueous mopping.

SECTION 7 - HANDLING AND STORAGE

For best product stability, avoid freezing and higher than normal ambient temperatures.

SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION: None required under normal use. When sanding or spraying, use a NIOSH P100 dust and mist respirator. If conditions warrant, a vapor respirator for protection against ammonia may be used.

VENTILATION: General dilution ventilation is recommended at a level sufficient to keep individuals asymptomatic to inhalation exposure.

PROTECTIVE GLOVES: None required under normal use. For techniques requiring continual hand exposure, gloves are recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required under normal use.

WORK/HYGIENIC PRACTICES: Used in accordance with safe handling practices, including: do not eat, drink or smoke when working with materials, avoid excessive skin contact, wash after working with materials.

SECTION 9 - PHYSICAL/CHEMICAL PROPERTIES

BOILING POINT: >100°C/212°F

SPECIFIC GRAVITY (H₂O=1): 1.09-1.28

VAPOR DENSITY: Heavier than air

pH: 8.5-9.2

SOLUBILITY IN WATER: Miscible

APPEARANCE AND ODOR: Milky white or colored- slight ammonia odor

VOC: <50 g/l

SECTION 10 - STABILITY AND REACTIVITY

STABILITY: Stable

INCOMPATIBILITY: May react with strong oxidizers

HAZARDOUS DECOMPOSITION OR BYPRODUCTS Ultramarine Blue acids to form flammable and toxic hydrogen sulfide.

SECTION 11 – TOXICOLOGICAL INFORMATION

Product not evaluated as a whole. Classification based on individual components.

SECTION 12 – ECOLOGICAL INFORMATION

Not readily biodegradable. No other data available.

SECTION 13 – DISPOSAL CONSIDERATIONS

Dispose as per local regulations. It is best to use all material, rather than dispose of it. If necessary, dispose of as latex paint.

SECTION 14 -TRANSPORT INFORMATION

Not hazardous for shipping via any mode

SECTION 15 – REGULATORY INFORMATION

Contact us for further information.

SECTION 16 – OTHER INFORMATION

7/12/2018 New