

Pro Finishes™ Matting Additive

000D205

Technical Data Sheet – Page 1 of 2

Description

GOLDEN Pro Finishes Matting Additive is a complementary product to other Pro Finishes and Golden Paintworks Lifestyle Finishes products. Pro Finishes Matting Additive will decrease the sheen of other products.

Key Features

- 100% acrylic waterborne formulation
- Compatible with most water-based paints, mediums, or textures
- Ready to use
- Water clean up

Preparation

Before opening a container of Pro Finishes Matting Additive, shake the container to make the product homogenous and smooth. Failure to properly shake the product can result in an uneven consistency.

Application:

- Shake or stir thoroughly before use.
- Formulated as an additive only, do not use stand-alone.
- Use a maximum 10% (1:10) matting additive to compatible material.
- Always mix thoroughly until the product has been evenly distributed.
- Always test ratio before use.
- Test your technique on a practice board before applying to walls
- DO NOT USE with solvent-based materials
- For interior use only.

Clean Up

Clean your skin and equipment immediately after use with soap and warm water. Keep tools wet while working. Dispose of as latex paint.

Storage

- Store in a cool/dry location @ temperatures between 40° F & 90° F.
- Do not allow material to freeze or be exposed to temperatures exceeding 120° F for extended periods.

Packaging

8 fl. oz. / 237 ml Bottle

Physical/Performance Property

Weight per Gallon (in lbs)
Specific Gravity
Typical Weight Solids
Typical Volume Solids
Consistency/Appearance
pH (initial)
Viscosity
Odor
Gloss/Sheen
Base Polymer
Flash Point
Freeze/Thaw Stability
Shelf Life
Storage Conditions
Application Temperature
Paintability
Application Thinner
Clean Up
Coverage Per Gallon

Test Method

Gardner Cup
Calculated
Calculated
Calculated
Visual Observation
pH Meter
Brookfield RVT
Subjective
Glossmeter
Known
Closed Cup
Lab Test
Lab Test
Recommendation
Recommendation
Recommendation
Recommendation
Recommendation

Typical Result

9.28
1.11
37%
32%
White Liquid
8.7 – 9.3
3,000 – 5,000 cP (spindle 6, 100 rpms)
Slight ammonia
NA
100% Acrylic
None (water based)
Pass: 5 Cycles
Expect 2 Years @ 77° F
Cool/Dry, Avoid Freezing/Heat
50° F to 90° F (best results)
NA
Thins with water
Warm, soapy water
NA



Golden Artist Colors, Inc., New Berlin, New York 13411
607-847-6154 www.goldenpaintworks.com

Pro Finishes™ Matting Additive
000D205

Technical Data Sheet – Page 2 of 2

Environmental & Transportation Information

VOC: 465 g/l
Not RCRA Hazardous for disposal. Dispose of as latex paint.
Not Dangerous Goods for shipping via any mode.

SEE SDS FOR ADDITIONAL INFORMATION

LIMITED WARRANTY

In the unlikely event of product failure, and determination by GOLDEN that product did not meet intended quality or published specifications, GOLDEN will, at its discretion, either replace the product or refund the purchase price as the customer's sole remedy. GOLDEN expressly disclaims liability for incidental and consequential damages, to the extent allowed by law.

TDS Number: TDSD205

Date of Issue: October 10, 2017